

TRAIL 650B

SIXFIFTY 6500



FEATURES

11 speed
Sram GX1 drivetrain
KS E10 Integra Seatpost
WTB Tubeless Ready Wheelset

NEW OR CHANGED FOR 2017


Rock Shox Sektor Gold RL Fork
WTB STP-I23 TCS, Disc, Tubeless Ready Rims
Sram GX 1 Drivetrain
Kore Durox 35mm Handlebar
Shimano M506 Hydraulic Disc Brakes

BIKE SPECS

Frame	FSS 650B 140mm, Alloy 6061 w/Custom Formed Dbl.Buttet TT & DT, 1.5 Taper, 12 x 142 rear axle, w/replaceable derailleur hanger
Rear Shock	Rock Shox Monarch RT3, KHS Tuned, Solo air w/High Volume Eyelet, 3 Pos. Switch= Open/Pedal/Lock, Rebound adj.
Fork	Rock Shox Sektor Gold RL, 140mm, 1-1/8-1.5 Tapered Alloy Steerer, External Rebound, Low Speed Compression to 'Lock' , 15mm Through Axle
Headset	FSA Orbit 1.5E, Zero Stack, 1 1/8"~1.5
Rims	WTB STP-I23 TCS, Disc, Double Wall, 28H, Tubeless Ready
Hub, Front	Light Weight S/B Alloy Disc, 15mm, Straight Pull
Hub, Rear	Light Weight S/B Alloy Disc, XD Driver, 12 x 142mm, Straight Pull
Tires	Maxxis High Roller II, 27.5 X 2.3, 60 TPI Folding, 3C/EXO/TR, Tubeless Ready
Spokes	14G/15G Double Butted Black Stnls w/Alloy Nipples, 28x28
Derailleur, Rear	Sram GX 1, 11s X-Horizon, Type 2
Shifters	Sram GX 1, 11s Trigger, Right Only
Chain	SRAM PC-1130
Crankset	SRAM GX 1000, X-Sync, 2 pc., GXP, 32T, S: 170, M-XL: 175
BB	Sram GXP-XR, Outboard Bearing
Freewheel / Cassette	Sram XG-1150, 10-42T, 11-speed
Seatpost	Kind Shock E10I, Integra w/Remote, Travel Adj, 31.6 x 420mm
Saddle	WTB Volt Comp
Handlebar	Kore Durox 35mm, 760mm X 20mm
Stem	Kore Cubix 35mm 3D Forged, S: 50mm, M-L: 60mm, XL: 70mm
Grips	Q2 Lock-on
Brake Levers	Shimano M506, Servo Wave
Brakes	Shimano M506 Hydraulic Disc, 180/160mm Rotors
Color	Matte Black
Frame Size	S/15, M/16.5, L/18, XL/20

PART # MODEL SIZE COLOR

97-151-000	SixFifty 6500	S/15	Matte Black
97-151-001	SixFifty 6500	M/16.5	Matte Black
97-151-002	SixFifty 6500	L/18	Matte Black
97-151-003	SixFifty 6500	XL/20	Matte Black



GEOMETRY

SIZE	A s/tc-t	B h/t°	C s/t°	D eff. c/s	E c/s	F Bl.ight	H s.o.	I lh/t	K Stack	J Reach
S/15	380.5	67.5°	75°	523	430.6.9	342.3.5	746.9.4	1104.3	585.23	428.16.9
M/16.5	420.5	67.5°	75°	605.8	430.6.9	342.3.5	762.0	1104.3	585.23	448.17.6
L/18	460.8.1	67.5°	75°	625.6	430.6.9	342.3.5	783.0.9	1204.7	594.23.4	468.8.3
XL20	500.9.7	67.5°	75°	645.4	430.6.9	342.3.5	818.1.9	1305.1	602.3.7	483.9

All specs are subject to change without notice.

