

# TRAIL 650B SIXFIFTY 6600C

**Nuevo Modelo**




## FEATURES

- 11 speed
- MSD Carbon
- Sram GX1 drivetrain
- KS E10 Integra Seatpost

PART #	MODEL	SIZE	COLOR
97-153-000	SixFifty 6600 (Carbon)	S/16	Matte Orange/Black
97-153-001	SixFifty 6600 (Carbon)	M/17.5	Matte Orange/Black
97-153-002	SixFifty 6600 (Carbon)	L/19	Matte Orange/Black
97-153-003	SixFifty 6600 (Carbon)	XL/20.5	Matte Orange/Black

## BIKE SPECS

Frame	MSD/MLS Full Carbon, 650B, 150mm, 1.5 Taper, 12 x 142 Rear Axle, w/Replaceable Derailleur Hanger
Rear Shock	Rock Shox Monarch RT3, KHS Tuned, Solo air w/High Volume Eyelet, 3 Pos. Switch= Open/Pedal/Lock, Rebound adj.
Fork	Rock Shox Pike RCT3, 150mm, Solo Air, 1.5 Taper, 15mm Thru-Axle, External Rebound, Low Speed Compression, 3 Position Compression
Headset	FSA Orbit 1.5E, Zero Stack, 1 1/8"~1.5
Rims	WTB STP-I25 TCS, Disc, Double Wall, 28H, Tubeless Ready
Hub, Front	Light Weight S/B Alloy Disc, 15mm, Straight Pull
Hub, Rear	Light Weight S/B Alloy Disc, XD Driver, 12 x 142mm, Straight Pull
Tires	Maxxis High Roller II, 27.5 X 2.3, 60 TPI Folding, 3C/EXO/TR, Tubeless Ready
Spokes	14G/15G Double Butted Black Stnls w/Alloy Nipples, 28x28
Derailleur, Rear	Sram GX 1, 11s X-Horizon, Type 2
Shifters	Sram GX 1, 11s Trigger, Right Only
Chain	SRAM PC-1130
Crankset	SRAM GX 1000, X-Sync, 2 pc., PF92, 30T, S: 170, M-XL: 175
BB	PF92
Freewheel / Cassette	Sram XG-1150, 10-42T, 11-speed
Seatpost	Kind Shock E10I, Integra w/Remote, Travel Adj, 31.5 x 420mm
Saddle	WTB Volt Sport
Handlebar	Kore Durox, 760mm X 20mm, 31.8
Stem	Kore Repute, S: 35mm, M-XL: 50mm
Grips	Q2 Lock-On
Brake Levers	Shimano SLX
Brakes	Shimano SLX M675 Hydraulic Disc, 180/160
Color	Matte Orange/Black
Frame Size	S/16, M/17.5, L/19, XL/20.5



## GEOMETRY

SIZE	A s/tc-t	B h/t°	C s/t°	D effectv	E c/s	F Wheel	H s.o.	I lb/t	K Stack	J Reach					
S/16	400	5.7	68°	74°	520.8	440	7.3	349	3.7	TBD	1009	59	123.3	413	6.3
M/17.5	445	7.5	68°	74°	620.6	440	7.3	349	3.7	TBD	1103	59	123.3	430	6.9
L/19	483	9	68.5°	74°	620.4	440	7.3	349	3.7	TBD	1207	60	123.3	447	7.6
XL/20.5	520	5	68.5°	74°	620.2	440	7.3	349	3.7	TBD	1301	61	124.1	464	8.3

All specs are subject to change without notice.

