

TRAIL 650B SIXFIFTY 6700C

Nuevo modelo




FEATURES

- 11 speed
- MSD Carbon Frame
- Sram XO1 drivetrain
- KS Lev DX Integra Seatpost

BIKE SPECS

Frame	MSD/MLS Full Carbon, 650B, 150mm, 1.5 Taper, 12 x 142 Rear Axle, w/Replaceable Derailleur Hanger
Rear Shock	FOX Factory Float DPS W/EVOL, Air, CTD 3-pos Lever, Rebound Adj, w/Kashima Coat
Fork	Fox Factory 34 Float 27.5", FIT4 CTD 3-Pos. Lever W/Adj, w/ Kashima Coat, 150mm, Air, External Rebound, CTD Low Speed Compression, 1.5 Taper, 15mm Thru Axle
Headset	FSA Orbit 1.5E, Zero Stack, 1 1/8"~1.5
Rims	DT M1700 Spline Wheel Set, 650B Disc, Straight Pull w/ 15mm Thru-Axle Ft, 12 x 142mm Rear, Tubeless Ready
Hub, Front	DT M1700 Spline Wheel set.
Hub, Rear	DT M1700 Spline Wheel set.
Tires	Maxxis High Roller II, 27.5 X 2.3, 60 TPI Folding, 3C/EXO/TR, Tubeless Ready
Spokes	DT M1700 Spline Wheel set.
Derailleur, Rear	Sram XO 1, 11s X-Horizon, Type 2
Shifters	Sram XO 11s Trigger, Right Only
Chain	Sram PC-1130
Crankset	Sram X1 1400 X-Sync, Hollow Forged, PF92, 30T S: 170, M-XL: 175
BB	PF92
Freewheel / Cassette	Sram XG-1150, 10-42T, 11-speed
Seatpost	Kind Shock LEV DX Integra w/Remote, Travel Adjust, Internal Routing, 31.6x392mm
Saddle	WTB High Tail, CrMo Rail
Handlebar	Q2 Carbon Riser, 740mm x 31.8
Stem	Kore Repute, S: 35mm, M-XL: 50mm
Grips	Q2 Lock-on
Brake Levers	Sram Guide RSC, Match Maker X
Brakes	Sram Guide RSC Hydraulic Disc, 4 Piston, Tool Free Reach & Pad Contact Adj., 180/160mm Rotors
Color	Black w/ yellow
Frame Size	S/16, M/17.5, L/19, XL/20.5

PART #	MODEL	SIZE	COLOR
97-154-000	SixFifty 6700 (Carbon)	S/16	Black w/ yellow
97-154-001	SixFifty 6700 (Carbon)	M/17.5	Black w/ yellow
97-154-002	SixFifty 6700 (Carbon)	L/19	Black w/ yellow
97-154-003	SixFifty 6700 (Carbon)	XL/20.5	Black w/ yellow



GEOMETRY

SIZE	A s/tc-t	B h/t°	C s/t°	D efflectv	E c/s	F Blight	H s.o.	I lh/t	K Stack	J Reach					
S/16	400	5.7	68°	74°	520.8	440	7.3	349	3.7	TBD	1009	59	123.3	413	6.3
M/17.5	445	5.5	68°	74°	620.6	440	7.3	349	3.7	TBD	1103	59	123.3	430	6.9
L/19	483	9	68.5°	74°	620.4	440	7.3	349	3.7	TBD	1207	60	123.7	447	7.6
XL/20.5	520	5	68.5°	74°	620.2	440	7.3	349	3.7	TBD	1301	61	124.1	464	8.3

All specs are subject to change without notice.

