

XC RACING

TEAM 29




FEATURES

12 Speed
MSD Carbon frame
Sram Eagle 1x12 speed drivetrain
Rock Shox SID RLC fork

NEW OR CHANGED FOR 2017

Sram X01 Eagle Rear Derailleur
Sram X01 Eagle, Trigger, Right Only Shifters
Sram X01 Eagle Carbon, Direct Mount Cranks
Sram XG-1295, 10-50T, 12s cassette
WTB SL8 Pro Saddle
FSA K-Force, Carbon, handlebar
FSA SLK, 3-D stem

PART #	MODEL	SIZE	COLOR
97-165-000	Team 29	S/15.5	Team
97-165-001	Team 29	M/17	Team
97-165-002	Team 29	L/19	Team



GEOMETRY

SIZE	A s/tc-t	B h/t°	C s/t°	D eff. c/s	E c/s	F Blight	H s.o.	I lh/t	K Stack	J Reach
S/15.5	395.6	69.5°	73°	580.8	440.7	310.2	769.0	100.9	612.4	387.5
M/17	440.7	69.5°	73°	600.6	440.7	310.2	799.1	109.1	618.4	405.9
L/19	483.9	69.5°	73°	620.4	440.7	310.2	830.2	120.7	632.4	420.6

BIKE SPECS

Frame	KHS Full MSD Carbon 29er w/1.5 Taper Headtube, Disc Only, Internal Cable Routing, 12x142
Fork	Rock Shox SID RLC 29", Charger Damper, 100mm Solo Air, External Rebound, Oneloc Remote, Low Speed Compression Adj, 1.5 Taper, 15mm x 110mm Boost Thru Axle
Headset	FSA Orbit C-40-CF-ACB, N.42/CF/ACB, 1-1/8"~1.5" Integrated
Rims	DT X1900 Spline Wheel Set, 29" Disc, Straight Pull w/ 15mm Ft & 12mm RR Thru-Axle, Tubeless Ready
Hub, Front	DT X 1900 SPLINE, 15mm x 110, Wheel Set
Hub, Rear	DT X 1900 Spline, 12mm x 142, Wheel Set
Tires	Maxxis Ikon 3C Maxx Speed, 120TPI Folding, Triple Compound, Tubeless Ready, 29X2.2
Spokes	DT X 1900 Spline, Wheel set
Derailleur, Rear	Sram X01 Eagle, 12s X-Horizon, Type 3
Shifters	Sram X01 Eagle, 12s, Trigger, Right Only
Chain	Sram X01 Eagle 12s, PowerLock
Crankset	Sram X01 Eagle Carbon, Direct Mount, PF30, 34T S: 170, M-L: 80mm
BB	Sram PF-30
Freewheel / Cassette	Sram XG-1295, 10-50T, 12-speed
Seatpost	Q2 Team Full Carbon, 31.6X350mm
Saddle	WTB SL8 Pro
Handlebar	FSA K-Force Flat Riser, Carbon, 720mm, 31.8 x 5mm
Stem	FSA SLK, 3-D Forged CNC, +/- 6D, 4-Bolt, 31.8 S: 70mm, M-L: 80mm
Grips	Q2 Lock-on
Brake Levers	Sram Level TL, Match Maker X
Brakes	Sram Level TL Hydraulic Disc, 2 Piston, 180/160mm Rotors
Color	TEAM
Frame Size	S/15.5, M/17, L/19

All specs are subject to change without notice.

